


DECLARATION OF CONFORMITY



Macel authorises the affixing of CE marking in the following products in accordance with Annex ZA of the standard EN 13748-2:

Type of Tile	Terrazzo Tiles for External Use – Thickness Class I (Th I)														
	Bujardado			Relevo Polido				Anti-derrapante					Lavado		
	30x60x4,2	40x40x3,5 40x40x2,5	40x60x4,2	30x30x3,3	40x20x3,3 Calçada	26,1x30x3,3 Calçada 3D*	40x40x3,5 40x40x3,3 40x40x2,5	30x30x2,3	30x30x3,2	30x60x4,2	40x20x3,2 Calçada	40x40x3,5 40x40x3,3 40x40x2,5	40x60x4,2 40x60x4,0	40x40x3,5 40x40x2,3	40x60x4,0
Characteristics															
Breaking strength	ST	ST	ST	ST	ST	ST	ST	ST	ST	ST	ST	ST	ST	ST	ST
Breaking Load	3T	3T	3T	3T	3T	3T	3T	3T	3T	3T	3T	3T	3T	3T	3T
Weathering Resistance	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Abrasion Resistance	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F

* - Rhombus Format

Intended Uses	External Floorings
Reaction to fire	Class A1fl
External fire performance	Satisfactory
Slip/ Skid resistance	Satisfactory
Thermal conductivity (W/m.k)	NPD

Aguada de Cima, 15 April 2013

(Óscar Oliveira - Manager)